



Male Run Tee: TMT

connects **fractional** tube to female NPT thread



Metric fitting shown



Part Number*	T P		Dimensions — inches								
	Tube O.D.	Male NPT Size	B			C	D	E min	G	H	M
A	Hex Flat										
1TMT1[]	1/16	1/16	1.50	5/16	7/16	.41	.05	.56	.72	.78	
2TMT2[]	1/8	1/8	1.69	7/16	7/16	.56	.09	.66	.72	.97	
3TMT2[]	3/16	1/8	1.75	1/2	7/16	.59	.13	.69	.75	1	
4TMT2[]	1/4	1/8	1.83	9/16	7/16	.64	.19	.72	.78	1.05	
4TMT4[]	1/4	1/4	2.13	9/16	1/2	.64	.19	.78	1.02	1.11	
6TMT4[]	3/8	1/4	2.19	11/16	1/2	.72	.30	.84	1	1.19	
6TMT6[]	3/8	3/8	2.42	11/16	11/16	.72	.30	.94	1.13	1.30	
8TMT6[]	1/2	3/8	2.56	7/8	11/16	.99	.42	.97	1.13	1.44	
8TMT8[]	1/2	1/2	2.81	7/8	13/16	.99	.42	1.03	1.31	1.50	
10TMT8[]	5/8	1/2	2.84	1	13/16	1	.50	1.03	1.38	1.47	
12TMT12[]	3/4	3/4	3.09	1 1/8	1	1	.66	1.16	1.50	1.59	
14TMT12[]	7/8	3/4	3.22	1 1/4	1 1/4	1.06	.72	1.28	1.50	1.72	
16TMT12[]	1	3/4	3.53	1 1/2	1 1/4	1.31	.72	1.31	1.66	1.88	
16TMT16[]	1	1	3.72	1 1/2	1 1/4	1.31	.88	1.31	1.84	1.88	

Male Run Tee: TMT/ME

connects **metric** tube to female NPT threads

Part Number*	T S		Dimensions — mm								
	Tube O.D.	Pipe Thd.	B			C	D	E min	G	H	M
A	Hex Flat										
3TMT2[]ME	3	1/8	43.0	11.1	11.1	14.3	2.2	16.8	18.3	24.7	
6TMT2[]ME	6	1/8	46.4	14.3	11.1	16.3	3.8	18.2	17.8	26.6	
6TMT4[]ME	6	1/4	54.1	14.3	12.7	16.3	3.8	19.8	25.9	28.2	
6TMT6[]ME	6	3/8	59.4	14.3	17.5	16.3	3.8	22.4	28.7	30.7	
6TMT8[]ME	6	1/2	67.0	14.3	20.7	16.3	3.8	25.4	33.3	33.8	
8TMT2[]ME	8	1/8	49.3	15.9	12.7	16.7	4.7	20.6	20.6	28.6	
8TMT4[]ME	8	1/4	58.0	15.9	17.5	16.7	5.9	21.6	25.4	32.6	
10TMT2[]ME	10	1/8	58.0	19.1	17.5	17.5	4.7	24.6	25.4	32.6	
10TMT4[]ME	10	1/4	61.1	19.1	17.5	17.5	7.5	24.6	25.4	32.6	
10TMT6[]ME	10	3/8	61.3	19.1	17.5	17.5	8.0	24.6	28.7	32.6	
12TMT4[]ME	12	1/4	61.9	22.2	17.5	24.6	7.5	24.6	25.4	36.5	
12TMT8[]ME	12	1/2	71.5	22.2	19.8	24.6	10.0	26.2	33.3	38.2	